




**ALLIANCE
 CONSTRUCTION &
 INDUSTRIAL**

TRA: **R-4**
 Speed Rating: **A8**



Alliance 570 is an ideal radial tire for industrial and construction services. The tread pattern enables strong grip and high traction performances on soft surfaces, as well as comfortable work on hard surfaces and stable running on the roads. The strong polyester construction enables higher vehicle speed as well as increased puncture protection. Flatter tread because of radial tire construction provides even pressure distribution, high productivity and optimal fuel consumption.

TRACTOR DIAGONAL - 17.5L-24

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
		Speed														
		Constant load						Cyclic Applications								
		Static kmph	10 kmph					30 kmph	40 kmph	50 kmph	10 kmph	30 kmph	40 kmph	50 kmph		
17.5L-24	W15L W14L	445	1250	573	3727	12PR	2.1	6140	3340	2720	2670	2430	4010	2860	2670	2430
						150A8 147B	2.6	6950	3780	3080	3020	2750	4530	3230	3020	2750
							3.1	7710	4190	3480	3350	3050	5030	3580	3350	3050

Note: This size is not available with steel belts. Available in polyester construction only. Recommended rim in red.

