




**ALLIANCE
 CONSTRUCTION &
 INDUSTRIAL**

TRA: **R-4**
 Speed Rating: **A8**



Alliance 570 is an ideal radial tire for industrial and construction services. The tread pattern enables strong grip and high traction performances on soft surfaces, as well as comfortable work on hard surfaces and stable running on the roads. The strong polyester construction enables higher vehicle speed as well as increased puncture protection. Flatter tread because of radial tire construction provides even pressure distribution, high productivity and optimal fuel consumption.

TRACTOR - 19.5LR24 Steel Belted

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load										
		SW mm	OD mm					Speed										
								Constant load					Cyclic Applications					
								Static kmph	10 kmph	30 kmph	40 kmph	50 kmph	10 kmph	30 kmph	40 kmph	50 kmph		
19.5LR24 Steel Belted	W16L W15L	495	1320	600	3912	149A8 146B	1.5	5540	3010	4460	2410	2190	3620	2580	2410	2190		
							2.2	6950	3780	3080	3020	2750	4530	3230	3020	2750		
							2.5	7480	4060	3320	3250	2960	4880	3480	3250	2960		
							2.7	8650	4700	3840	3760	3420	5640	4020	3760	3420		
							3	9200	5000	4080	4000	3640	6000	4280	4000	3640		
						156A8 153B												

Note: This size is available without steel belts. Available in polyester construction only. Recommended rim in red. ^ One way distance 600 m. Steel belt available in 156A8/153B only.

