



ALLIANCE
**EARTHMOVER &
 MINING**

TRA: **G-2/L-2**
 Speed Rating: **B**



Alliance 308 is a tire designed for rugged service on front-end loaders. Husky tread bars are sized and angled for maximum traction and specially contoured to resist tearing and chipping. The overlapping lugs ensure smooth rolling on any type of surface and the spacing between lugs provides self-cleaning properties. It is built with ozone and weather-resistant compounds and has a strong nylon construction.

Transport & Grader - 15.5-25 L2,G2

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
		SW mm	OD mm					Speed								
								15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph	45 kmph	50 kmph	55 kmph
15.5-25 L2,G2	12 12SDC	394	1277	564	3720	8PR	1.5	2130	2090	2050	2010	1970	1950	1910	1890	-
						141B	1.75	2880	2830	2780	2730	2680	2650	2630	2575	2500
						10PR	1.75	2380	2330	2290	2250	2200	2180	2140	2110	-
						146B	2	3140	3080	3020	2970	2910	2880	2860	2800	2720
							2.25	3360	3300	3240	3180	3120	3090	3060	3000	2910
						12PR	2	3190	3140	3080	3020	2960	2940	2900	2850	-
						149B	2.5	3640	3580	3510	3450	3380	3350	3310	3250	-
						14PR	2.75	3980	3910	3830	3760	3690	3660	3620	3550	3440
						152B	3	3160	3100	3050	2990	2930	2900	2840	2810	-

Note: For above mentioned size only 12 PR is active for production.

Grader application

