




ALLIANCE **AGRICULTURE**

TRA: **R-1W** Speed Rating: **D**



The advanced AGRIFLEX+ 372 Very Improved Flexion (VF) designed with increased sidewall flexibility enables the tire to carry (up to 40%) more at the same pressure as compared to a standard tractor radial. It offers a significantly large footprint leading to low soil compaction and a comfortable ride for the driver. The larger footprint enables high traction, reduces fuel costs and increases overall operational productivity. The R-1W pattern enables excellent grip as well as long tire life on hard surfaces.

TRACTOR - VF650/65R42

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load												
								Speed												
								TRACTOR												
		SW mm	OD mm					5 kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph	45 kmph	50 kmph	55 kmph	60 kmph	65 kmph
VF650/65R42	DW23B DW21B	650	1913	856	5596	174D	0.8	4960	4400	4200	4160	4120	4080	4040	4000	4000	4000	4000	4000	4000
							1	5580	4950	4725	4680	4635	4590	4545	4500	4500	4500	4500	4500	4500
							1.2	6045	5363	5119	5070	5021	4973	4924	4875	4875	4875	4875	4875	4875
							1.4	6758	5995	5723	5668	5614	5559	5505	5450	5450	5450	5450	5450	5450
							1.6	7440	6600	6300	6240	6180	6120	6060	6000	6000	6000	6000	6000	6000
							1.8	7626	6765	6458	6396	6335	6273	6212	6150	6150	6150	6150	6150	6150
							2	8308	7370	7035	6968	6901	6834	6767	6700	6700	6700	6700	6700	6700

