




ALLIANCE  
**AGRICULTURE**

TRA: **R-1W**  
 Speed Rating: **A8**



The advanced AGRIFLEX+ 372 Very Improved Flexion (VF) designed with increased sidewall flexibility enables the tire to carry (up to 40%) more at the same pressure as compared to a standard tractor radial. It offers a significantly large footprint leading to low soil compaction and a comfortable ride for the driver. The larger footprint enables high traction, reduces fuel costs and increases overall operational productivity. The R-1W pattern enables excellent grip as well as long tire life on hard surfaces.

**TRACTOR RADIAL HIGH SPEED - VF 620/75R30 CFO**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		SW mm	OD mm					Speed						
								CFO		Not high and sustained torque; Road transport				
								15 kmph	30 kmph	10 kmph	15 kmph	20 kmph	65 kmph	70 kmph
VF 620/75R30 CFO	DW23B DW21B DW20B	650	1675	720	4866	169D	0.8	4894	4085	3940	3680	3680	3680	3350
							1	5599	4673	4510	4210	4210	4210	3830
							1.2	6291	5250	5070	4730	4730	4730	4300
							1.4	6996	5839	5640	5260	5260	5260	4790
							1.6	7714	6438	6210	5800	5800	5800	5280

Highlighted column indicates speed limit 25kmph to 65kmph

