



**ALLIANCE
 AGRICULTURE**

TRA: **R-1W**
 Speed Rating: **D**



The advanced AGRIFLEX+ 372 Very Improved Flexion (VF) designed with increased sidewall flexibility enables the tire to carry (up to 40%) more at the same pressure as compared to a standard tractor radial. It offers a significantly large footprint leading to low soil compaction and a comfortable ride for the driver. The larger footprint enables high traction, reduces fuel costs and increases overall operational productivity. The R-1W pattern enables excellent grip as well as long tire life on hard surfaces.

TRACTOR - VF650/60R34

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
		SW mm	OD mm					Speed							
								TRACTOR APPLICATION							
								10 kmph	20 kmph	30 kmph	40 kmph	50 kmph	60 kmph	65 kmph	70 kmph
VF650/60R34	DW23BX34	650	1644	731	4845	168D	0.8	3575	3380	3315	3250	3250	3250	3250	2958
							1.2	4538	4290	4208	4125	4125	4125	4125	3754
							1.6	5665	5356	5253	5150	5150	5150	5150	4687
							2	6160	5824	5712	5600	5600	5600	5600	5096

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
		SW mm	OD mm					Speed	
								Cyclic operations	
								10 kmph	
VF650/60R34	DW23BX34	650	1644	731	4845	168D	1.6	4550	
							2	5775	
							2.4	7210	
							2.8	7840	

