



ALLIANCE
AGRICULTURE

TRA: **R-1W**
 Speed Rating: **A8**



The advanced AGRIFLEX+ 372 Very Improved Flexion (VF) designed with increased sidewall flexibility enables the tire to carry (up to 40%) more at the same pressure as compared to a standard tractor radial. It offers a significantly large footprint leading to low soil compaction and a comfortable ride for the driver. The larger footprint enables high traction, reduces fuel costs and increases overall operational productivity. The R-1W pattern enables excellent grip as well as long tire life on hard surfaces.

TRACTOR RADIAL HIGH SPEED - VF 600/65R28

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
								Speed						
		CFO						Not high and sustained torque; Road transport						
		15 kmph	30 kmph					10 kmph	15 kmph	20 kmph	65 kmph	70 kmph		
VF 600/65R28	DW21B DW20B DW18	606	1485	650	4382	163D	0.8	3840	3210	3100	2890	2890	2890	2630
							1.2	4950	4130	3990	3720	3720	3720	3390
							1.6	5870	4900	4730	4410	4410	4410	4010
							2	6480	5410	5220	4875	4875	4875	4440

