




**ALLIANCE
 CONSTRUCTION &
 INDUSTRIAL**

TRA: **R-4**
 Speed Rating: **A8**



Alliance 570 is an ideal radial tire for industrial and construction services. The tread pattern enables strong grip and high traction performances on soft surfaces, as well as comfortable work on hard surfaces and stable running on the roads. The strong polyester construction enables higher vehicle speed as well as increased puncture protection. Flatter tread because of radial tire construction provides even pressure distribution, high productivity and optimal fuel consumption.

TRACTOR - 425/55R17 Steel Belted

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
		SW mm	OD mm					Speed								
								Constant load					Cyclic Applications			
								Static kmph	10 kmph	30 kmph	40 kmph	50 kmph	10 kmph	30 kmph	40 kmph	50 kmph
425/55R17 Steel Belted	13	425	890	395	2663	140A8 140B	0.8	2420	1580	1120	1050	1050	1840	1160	1050	1050
							1	2760	1800	1280	1200	1200	2100	1320	1200	1200
							1.2	3060	2000	1420	1330	1330	2330	1460	1330	1330
							1.4	3360	2190	1560	1460	1460	2560	1610	1460	1460
							1.6	3630	2370	1690	1580	1580	2770	1740	1580	1580
							2	4140	2700	1930	1800	1800	3150	1980	1800	1800
							2.5	4720	3080	2190	2050	2050	3590	2260	2050	2050
							3	5240	3420	2440	2280	2280	3990	2510	2280	2280
3.5	5750	3750	2680	2500	2500	4380	2750	2500	2500							

Recommended rim in red. ^ One way distance 600 m. Steel belt available in **140A8/140B** only.

