



**ALLIANCE
 AGRICULTURE**

TRA: **R-1W**
 Speed Rating: **D**



The high speed rated AGRI STAR II comes with a Stratified Layer technology (SLT) - a unique combination of two layers: The top layer with a single angle profile and bottom layer with a multi-angle profile. After 40% wear of the tire, bottom layer of the lug comes in contact with the ground which leads to increased contact area at the central portion. This leads to better roadability and performance of the tire. The increased amount of rubber volume in AGRI STAR II enhances its stiffness that results in better wear resistance.

85 Series - 480/80R46

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
								Speed						
		Tractor Applications												
		SW mm	OD mm					Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph
480/80R46	DW16LX46	494	1960	909	5873	158D	0.8	5290	3450	2726	2645	2519	2415	2300
							1.2	6670	4350	3437	3335	3176	3045	2900
							1.6	8165	5325	4207	4083	3887	3728	3550
							2	8913	5813	4592	4456	4243	4069	3875
							2.4	9775	6375	5036	4888	4654	4463	4250

