


**ALLIANCE
CONSTRUCTION &
INDUSTRIAL**

TRA: **R-4**
Speed Rating: **A8**

TL

TUBE LESS

CUT &
CHIP RES
ISTANT C
OMPOUN
D

Alliance 570 is an ideal radial tire for industrial and construction services. The tread pattern enables strong grip and high traction performances on soft surfaces, as well as comfortable work on hard surfaces and stable running on the roads. The strong polyester construction enables higher vehicle speed as well as increased puncture protection. Flatter tread because of radial tire construction provides even pressure distribution, high productivity and optimal fuel consumption.

MPT - 495/70R24 Steel Belted

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
		SW mm	OD mm					Speed								
								10 kmph	20 kmph	30 kmph	40 kmph	50 kmph	60 kmph	70 kmph	80 kmph	90 kmph
495/70R24 Steel Belted	16	499	1304	588	3845	155G	3.6	6750	5630	4690	4310	4200	4130	4010	3900	3750
							3.8	6770	5640	4700	4320	4210	4140	4020	3910	3760
							4	6980	5810	4840	4460	4340	4260	4150	4030	3875

Recommended rim in red. Steel belt available in 155G only.

