



LOAD CERTIFICATE : 650/75R32 Steel Belted

Brand: ASCENSO

Tread Pattern : HRR 200

LSI: 172 A8

Tyre Construction: Radial

Type: Tubeless

Main Applications: Harvester

TRA Code : R-1



Salient Features

- Pattern optimised for **quiet running**
- Optimized carcass for **better operational stability, roadability and manoeuvring**
- Specially designed compound suitable for **high load carrying capacity**



Technical Specification

Size	Rim	Unloaded dimension		Loaded Static	Rolling Circumference	Load Index	Infl.	Recommended load, kg (lbs)						
		SW	OD	Radius			press.	Speed, km/h (mph)					High Torque	Cyclic Application
		mm	mm	mm	mm	Speed	bar	10	15	25	30	40	10	10
		in	in	in	in	Symbol	psi	6	9	16	19	25	6	6
650/75R32 Steel Belted	DW21B	655	1789	809	5351	172 A8	1.6	6870	6140	5440	4900	4580	4900	---
							23	15130	13520	11980	10790	10090	10790	
							2.0	7530	6730	5960	5370	5020	5370	
							29	16590	14820	13130	11830	11060	11830	
							2.4	8030	7170	6350	5720	5350	5720	
							35	17690	15790	13990	12600	11780	12600	
							2.8	8790	7850	6960	6270	5860	6270	
							41	19360	17290	15330	13810	12910	13810	
							3.2	9450	8440	7480	6740	6300	6740	
							46	20810	18590	16480	14850	13880	14850	
							4	---	---	---	---	---	---	
58	---	---	---	---	---	---	23590							

Note: All tyres confirm to ETRTO standards

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover