



LOAD CERTIFICATE : 800/65R32 Steel Belted

Brand: ASCENSO

Tread Pattern : HRR 200

LSI : 181 A8

Tyre Construction: Radial

Type: Tubeless

Main Applications: Harvester

TRA Code : R-1



Salient Features

- Pattern optimised for **quiet running**
- Optimized carcass for **better operational stability, roadability and manoeuvring**
- Specially designed compound suitable for **high load carrying capacity**



Technical Specification

Size	Rim	Unloaded dimension		Loaded Static	Rolling Circumference	Load Index	Infl.	Recommended load, kg (lbs)							
		SW	OD	Radius			press.	Speed, km/h (mph)					High Torque	Cyclic Application	
		mm	mm	mm	mm	Speed	bar	10	15	25	30	40			10
		in	in	in	in	Symbol	psi	6	9	16	19	25	6	6	
800/65R32 Steel Belted	DW27B	818	1853	835	5542	181 A8	2.0	8750	7810	6930	6240	5830	6240	---	
							29	19270	17200	15260	13740	12840	13740		
							2.4	9450	8440	7480	6740	6300	6740		
							35	20810	18590	16480	14850	13880	14850		
							2.8	10340	9230	8180	7370	6890	7370		
							41	22780	20330	18020	16230	15180	16230		
							3.2	11150	9960	8820	7950	7430	7950		
							46	24560	21940	19430	17510	16370	17510		
							3.6	12380	11060	9800	8830	8250	8830		
							52	27270	24360	21590	19450	18170	19450		
							4.5	---	---	---	---	---	---		14030
							65	---	---	---	---	---	---		30900

Note: All tyres confirm to ETRTO standards

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover