



LOAD CERTIFICATE : 900/60R32 Steel Belted

Brand: ASCENSO

Tread Pattern : HRR 200

LSI : 191 D

Tyre Construction: Radial

Type: Tubeless

Main Applications: Harvester

TRA Code : R-1



Salient Features

- Pattern optimised for **quiet running**
- Optimized carcass for **better operational stability, roadability and manoeuvring**
- Specially designed compound suitable for **high load carrying capacity**



Technical Specification

Size	Rim	Unloaded dimension		Loaded Static	Rolling Circumference	Load Index	Infl.	Recommended load, kg (lbs)									
		SW	OD	Radius				Speed	Harvester Application						High Torque	Cyclic Application	
		mm	mm	mm					bar	10	15	25	30	40			65
		in	in	in					psi	6	9	16	19	25	40	6	6
900/60R32 Steel Belted	DW28B	896 35.2	1893 74.5	852 33.5	5662 222.9	191 D	2.8	11580	10340	9150	8880	8450	7720	8880	---		
							41	25510	22780	20150	19560	18610	17000	19560			
							3.2	12480	11150	9860	9570	9110	8320	9570			
							46	27490	24560	21720	21080	20070	18330	21080			
							3.6	13290	11870	10500	10190	9700	8860	10190			
							52	29270	26150	23130	22440	21370	19520	22440			
							4.0	14000	12500	11060	10730	10220	9330	10730			
							58	30840	27530	24360	23630	22510	20550	23630			
							4.4	16350	14610	12920	12540	11940	10900	12540			
							64	36010	32180	28460	27620	26300	24010	27620			
							5.5	---	---	---	---	---	---	---		---	18530
							80	---	---	---	---	---	---	---		---	40810

Note: All tyres confirm to ETRTO standards

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover