



FTB 190 : 400/60 – 15.5

Brand: ASCENSO

Tread Pattern : FTB 190

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Baler and Trailers

TRA Code : I-3



Salient Features

Optimized Flotation Design:

- Reduces soil compaction
- Generates traction
- Better self cleaning properties

Enhanced Carcass Construction:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Recommended load , kg (lbs)								
		SW	OD				Speed , km/h (mph)								
		mm	mm				Free rolling				Drive wheel				
		mm	mm				Bar	10	25	40	50	10	25	40	50
		In	in				Psi	6	16	25	31	6	16	25	31
400/60-15.5	13	404 15.9	874 34.4	395 15.5	2614 102.9	16 PR 145 A8 FR 132 A8 DW	2.7	3430	2920	2450	2210	2370	2010	1690	1521
							39	7546	6424	5390	4862	5214	4422	3718	3346
							3	3650	3110	2610	2350	2520	2140	1800	1620
							44	8030	6842	5742	5170	5544	4708	3960	3564
							3.3	3860	3280	2760	2480	2660	2260	1900	1710
							48	8492	7216	6072	5456	5852	4972	4180	3762
							3.6	4060	3450	2900	2610	2800	2380	2000	1800
							52	8932	7590	6380	5742	6160	5236	4400	3960

Note: All tyres confirm to ETRTO standards