



FTB 190 : 400/55-22.5

Brand: ASCENSO

Tread Pattern : FTB 190

Ply Rating : 14

Tyre Construction: Bias

Type: Tube Less

Main Applications: Baler and Trailers

TRA Code : I-3



Salient Features

Optimized Flotation Design:

- Reduces soil compaction
- Generates traction
- Better self cleaning properties

Enhanced Carcass Construction:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Recommended load , kg (lbs)								
		SW	OD				Speed , km/h (mph)								
		mm	mm				Free rolling				Drive wheel				
		In	in				mm	mm	Bar	10	25	40	50	10	25
				mm	mm	Psi	6	16	25	31	6	16	25	31	
400/55-22.5	13	404 15.9	1020 40.2	471 18.5	3051 120.1	14 PR 150 A8 FR 146 B FR 138A8 DW 134 B DW	2.3	4020	3420	2870	2580	2830	2400	2020	1818
							33	8844	7524	6314	5676	6226	5280	4444	4000
							2.5	4210	3580	3010	2710	2970	2520	2120	1908
							36	9262	7876	6622	5962	6534	5544	4664	4198
							2.7	4410	3750	3150	2840	3110	2640	2220	1998
							39	9702	8250	6930	6248	6842	5808	4884	4396
							3	4690	3990	3350	3020	3300	2810	2360	2124
							44	10318	8778	7370	6644	7260	6182	5192	4673

Note: All tyres confirm to ETRTO standards