



# LOAD CERTIFICATE: 500/60 – 22.5

**Brand:** ASCENSO

**Tread Pattern :** FTB 190

**Ply Rating :** 16

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Baler and Trailers

**TRA Code :** I-3



## Salient Features

### **Optimized Flotation Design:**

- Reduces soil compaction
- Generates traction
- Better self cleaning properties

### **Enhanced Carcass Construction:**

Ensures high load carrying capacity



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Recommended load , kg ( lbs)								
		SW	OD				Speed , km/h ( mph)								
		mm	mm	Free rolling				Drive wheel							
		in	in	mm	mm		Bar	10	25	40	50	10	25	40	50
				in	in		Psi	6	16	25	31	6	16	25	31
500/60-22.5	16	503 19.8	1172 46.2	534 21.0	3506 138.0	16 PR 162 A8 FR 150 A8 DW	2.5	5750	4890	4110	3770	4060	3450	2900	2610
							36	12650	10758	9042	8140	8932	7590	6380	5742
							2.7	6020	5120	4300	3870	4240	3610	3030	2727
							39	13244	11264	9460	8514	9328	7942	6666	5999
							2.9	6270	5330	4480	4030	4420	3760	3160	2844
							42	13794	11726	9856	8866	9724	8272	6952	6257
							<b>3.2</b>	<b>6650</b>	<b>5650</b>	<b>4750</b>	<b>4280</b>	<b>4690</b>	<b>3990</b>	<b>3350</b>	<b>3015</b>
							<b>46</b>	<b>14630</b>	<b>12430</b>	<b>10450</b>	<b>9416</b>	<b>10318</b>	<b>8778</b>	<b>7370</b>	<b>6633</b>

**Note:** All tyres confirm to ETRTO standards