



LOAD CERTIFICATE: 550/60 – 22.5

Brand: ASCENSO

Tread Pattern : FTB 190

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Baler and Trailers

TRA Code : I-3



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Recommended load , kg (lbs)								
							Speed , km/h (mph)								
		SW	OD				Free rolling				Drive wheel				
		mm	mm				10	25	40	50	10	25	40	50	
		In	in				in	in	in	in	in	in	in	in	
550/60-22.5	16	553 21.7	1240 48.8	562 22.2	3709 146.0	16 PR 166 A8 FR 154 A8 DW	2.3	6340	5390	4530	4080	4490	3820	3210	2889
							33	13948	11858	9966	8976	9878	8404	7062	6356
							2.5	6660	5660	4760	4280	4720	4010	3370	3033
							36	14652	12452	10472	9416	10384	8822	7414	6673
							2.7	6970	5930	4980	4480	4940	4200	3530	3177
							39	15334	13046	10956	9856	10868	9240	7766	6989
							3	7420	6310	5300	4770	5250	4460	3750	3375
							44	16324	13882	11660	10494	11550	9812	8250	7425

Note: All tyres confirm to ETRTO standards

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com