



LOAD CERTIFICATE: 600/55-26.5

Brand: ASCENSO

Tread Pattern : FTB 190

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Baler and Trailers

TRA Code : I-3



Salient Features

Optimized Flotation Design:

- Reduces soil compaction
- Generates traction
- Better self cleaning properties

Enhanced Carcass Construction:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Recommended load , kg (lbs)								
							Speed , km/h (mph)								
		SW	OD				Free rolling				Drive wheel				
		Mm	mm				10	25	40	50	10	25	40	50	
		In	in				mm	mm	mm	mm	mm	mm	mm	mm	
600/55-26.5	20	611 24.1	1333 52.5	609 24.0	3987 157.0	16 PR 170 A8 FR 167 B FR 159 A8 DW 156 B DW	Bar	10	25	40	50	10	25	40	50
							Psi	6	16	25	31	6	16	25	31
							2	7210	6130	5150	4640	5250	4460	3750	3375
							29	15862	13486	11330	10208	11550	9812	8250	7425
							2.2	7630	6490	5450	4910	5540	4710	3960	3564
							32	16786	14278	11990	10802	12188	10362	8712	7841
							2.4	8020	6820	5730	5160	5840	4960	4170	3753
							35	17644	15004	12606	11352	12848	10912	9174	8257
2.6	8400	7140	6000	5400	6130	5210	4375	3938							
38	18480	15708	13200	11880	13486	11462	9625	8663							

Note: All tyres confirm to ETRTO standards

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com