



LOAD CERTIFICATE: 600/50 – 22.5

Brand: ASCENSO

Tread Pattern : FTB 190

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Baler and Trailers

TRA Code : I-3



Salient Features

Optimized Flotation Design:

- Reduces soil compaction
- Generates traction
- Better self cleaning properties

Enhanced Carcass Construction:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Recommended load , kg (lbs)										
		SW	OD				Speed , km/h (mph)										
							Free rolling				Drive wheel						
		mm	mm				mm	mm	Bar	10	25	40	50	10	25	40	50
		In	in				in	in	Psi	6	16	25	31	6	16	25	31
600/50-22.5	20	611 24.0	1172 46.2	534 21.0	3506 138.0	16 PR 165 A8 FR 153 A8 DW	2.2	6260	5320	4470	4020	4440	3770	3170	2853		
							32	13772	11704	9834	8844	9768	8294	6974	6277		
							2.4	6580	5590	4700	4230	4680	3970	3340	3006		
							35	14476	12298	10340	9306	10296	8734	7348	6613		
							2.6	6900	5890	4930	4440	4900	4170	3500	3150		
							38	15180	12914	10846	9768	10780	9174	7700	6930		
							2.8	7210	6130	5150	4640	5110	4340	3650	3285		
							41	15862	13486	11330	10208	11242	9548	8030	7227		

Note: All tyres confirm to ETRTO standards

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com