



FTB 190 : 600/55-22.5

Brand: ASCENSO

Tread Pattern : FTB 190

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Baler and Trailers

TRA Code : I-3



Salient Features

Optimized Flotation Design:

- Reduces soil compaction
- Generates traction
- Better self cleaning properties

Enhanced Carcass Construction:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Recommended load , kg (lbs)								
		SW	OD				Speed , km/h (mph)								
		Mm	mm				Free rolling				Drive wheel				
		In	in				mm	mm	Bar	10	25	40	50	10	25
				mm	mm	Psi	6	16	25	31	6	16	25	31	
600/55-22.5	20	611 24.0	1232 48.5	559 22	3685 145.7	16PR 169 A8 FR 166 B FR 156 A8 DW 153 B DW	2	6960	5910	4970	4470	4800	4080	3430	3087
							29	15312	13002	10934	9834	10560	8976	7546	6791
							2.2	7360	6260	5260	4730	5080	4320	3630	3267
							32	16192	13772	11572	10406	11176	9504	7986	7187
							2.4	7740	6580	5530	4980	5350	4550	3820	3438
							35	17028	14476	12166	10956	11770	10010	8404	7564
							2.6	8120	6900	5800	5220	5600	4760	4000	3600
							38	17864	15180	12760	11484	12320	10472	8800	7920

Note: All tyres confirm to ETRTO standards

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com