



LOAD CERTIFICATE: 10.0/75-15.3 (260/70-15.3)

Brand: ASCENSO

Tread Pattern : IMB 160

Ply Rating : 14

Tyre Construction: Bias

Type: Tube Less

Main Applications: Implements.

Balers and Trailer

TRA Code : I-2



New Product Release

Optimum Implement Design:

Minimises soil compaction and protects the grass land

Strong Nylon Carcass:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg (lbs)								
		SW	OD				Speed , km/h (mph)								
							Free rolling				Drive wheel				
		mm	mm				Bar	10	25	40	50	10	25	40	50
		In	in				Psi	6	16	25	31	6	16	25	31
10.0/75-15.3 (260/70-15.3)	9	264 10.6	760 29.9	348 13.7	2274 89.5	10 PR 123 A8 FR 111 A8 FW	3	1860	1580	1330	1200	1320	1120	940	846
							44	4092	3476	2926	2640	2904	2464	2068	1861
							3.3	1970	1680	1410	1270	1390	1180	990	891
							48	4334	3696	3102	2794	3058	2596	2178	1960
							3.6	2070	1760	1480	1330	1460	1240	1040	936
							52	4554	3872	3256	2926	3212	2728	2288	2059
							3.9	2170	1840	1550	1400	1530	1300	1090	981
						57	4774	4048	3410	3080	3366	2860	2398	2158	
						14 PR 130 A8 FR 118 DW	4.1	2240	1900	1600	1440	1570	1330	1120	1108
							59	4928	4180	3520	3168	3454	2926	2464	2218
							4.5	2370	2010	1690	1520	1650	1400	1180	1062
							65	5214	4422	3718	3344	3630	3080	2596	2336
							5	2520	2140	1800	1620	1750	1490	1250	1125
							73	5544	4708	3960	3564	3850	3278	2750	2475
5.5	2660	2260	1900	1710	1850		1570	1320	1188						
80	5852	4972	4180	3762	4070	3454	2904	2614							

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification