



IMB 160 :12.5/80-18

Brand: ASCENSO

Tread Pattern : IMB 160

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Implements.

Balers and Trailer

TRA Code : I-2



New Product Release

Optimum Implement Design:

Minimises soil compaction and protects the grass land

Strong Nylon Carcass:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg (lbs)								
		SW	OD				Speed , km/h (mph)								
		mm	mm	mm	mm	Free rolling				Drive wheel					
		in	in	in	in	Bar	10	25	40	50	10	25	40	50	
						LI/SI	Psi	6	16	25	31	6	16	25	31
12.5/80-18	9/11	308/328 12.2/12.9	965 38.0	439 17.3	2887 113.6	16 PR 148 A8 FR 135 A8 DW	3.7	3740	3180	2670	2400	2590	2200	1850	1665
							54	8228	6996	5874	5280	5698	4840	4070	3663
							4.1	3980	3380	2840	2560	2740	2330	1960	1764
							59	8756	7436	6248	5632	6028	5126	4312	3881
							4.5	4200	3570	3000	2700	2900	2460	2070	1863
							65	9240	7854	6600	5940	6380	5412	4554	4099
							4.9	4410	3750	3150	2840	3050	2590	2180	1962
							71	9702	8250	6930	6248	6710	5698	4796	4316

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification