



LOAD CERTIFICATE: 15.0/70-18

Brand: ASCENSO

Tread Pattern : IMB 160

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Implements.

Balers and Trailer

TRA Code : I-2



New Product Release

Optimum Implement Design:

Minimises soil compaction and protects the grass land

Strong Nylon Carcass:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg (lbs)								
		SW	OD				Speed , km/h (mph)								
		mm	mm	mm	mm	Free rolling				Drive wheel					
		In	in	in	in	LI/SI	Bar	10	25	40	50	10	25	40	50
						Psi	6	16	25	31	6	16	25	31	
15.0/70-18	13	391 15.4	990 38.9	449 17.6	2961 116.5	16 PR 151 A8 FR 139 A8 DW	3.3	4160	3530	2970	2670	2930	2490	2090	1881
							48	9152	7766	6534	5874	6446	5478	4598	4138
							3.6	4380	3720	3130	2820	3080	2620	2200	1980
							52	9636	8184	6886	6204	6776	5764	4840	4356
							3.9	4590	3900	3280	2950	3230	2750	2310	2079
							57	10098	8580	7216	6490	7106	6050	5082	4574
							4.25	4830	4110	3450	3110	3400	2890	2430	2187
62	10626	9042	7590	6842	7480	6358	5346	4811							

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification