



LOAD CERTIFICATE: 340/55-16

Brand: ASCENSO

Tread Pattern : IMB 161

Ply Rating : 12

Tyre Construction: Bias

Type: Tube Less

Main Applications: Balers and Trailer

TRA Code : I-2



Salient Features

Wider Footprint:

Minimises soil compaction and protects the grass land

Optimum Height to Width Ratio:

Ensures stability

Strong Nylon Carcass:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg (lbs)								
		SW	OD				Speed , km/h (mph)								
		mm	mm				Free rolling				Drive wheel				
		in	in				Bar	10	25	40	50	10	25	40	50
						LI/SI	Psi	6	16	25	31	6	16	25	31
340/55-16	11	343 13.5	780 30.7	358 14.0	2333 91.8	12 PR 133 A8 FR 121 A8 DW	2.5	2490	2120	1780	1600	1750	1490	1250	1125
							36	5478	4664	3916	3520	3850	3278	2750	2475
							2.7	2600	2210	1860	1670	1830	1560	1310	1179
							39	5720	4862	4092	3674	4026	3432	2882	2594
							2.9	2720	2310	1940	1750	1920	1630	1370	1233
							42	5984	5082	4268	3850	4224	3586	3014	2713
							3.2	2880	2450	2060	1850	2030	1730	1450	1305
							46	6336	5390	4532	4070	4466	3806	3190	2871

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com