



LOAD CERTIFICATE: 400/60-15.5

Brand: ASCENSO

Tread Pattern : IMB 161

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Balers and Trailer

TRA Code : I-2



Salient Features

Wider Footprint:

Minimises soil compaction and protects the grass land

Optimum Height to Width Ratio:

Ensures stability

Strong Nylon Carcass:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg (lbs)								
		SW	OD				Speed , km/h (mph)								
		mm	mm				Free rolling				Drive wheel				
		in	in				mm	mm	Bar	10	25	40	50	10	25
						Li/SI	Psi	6	16	25	31	6	16	25	31
400/60-15.5	13	404 15.9	874 34.4	395 15.5	2614 102.9	16 PR 148 A8 FR 135 A8 DW	3.2	3770	3200	2690	2420	2600	2210	1860	1674
							46	8294	7040	5918	5324	5720	4862	4092	3683
							3.5	3960	3370	2830	2550	2740	2330	1960	1764
							51	8712	7414	6226	5610	6028	5126	4312	3881
							3.8	4160	3530	2970	2670	2880	2450	4060	1854
							55	9152	7766	6534	5874	6336	5390	4532	4079
							4.2	4410	3750	3150	2840	3050	2590	2180	1962
							61	9702	8250	6930	6248	6710	5698	4796	4316

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification