



LOAD CERTIFICATE: 11.5/80-15.3

Brand: ASCENSO

Tread Pattern : IMB 162

Ply Rating : 12

Tyre Construction : Bias

Type : Tubeless

Main Applications: 2WD Tractor and Trailers

TRA Code : R-1



Salient Features

Specially Designed Directional Tread Pattern :

Ensures excellent traction & self cleaning properties

Superior Carcass Construction:

High load carrying capacity

Special Tread Compound:

Ensures longer tyre life



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	PR	Free/ Drive Wheel	Recommended load , kg (lbs)								
		SW	OD					Speed , km/h (mph)								
		Free rolling		Drive wheel												
		mm	mm	mm	mm			Bar	10	25	40	50	10	25	40	50
In	in	in	in	LI/SI	Psi	6	16	25	31	6	16	25	31			
11.5/80-15.3	9	290	867	392	2594	12	135A8 FR 123A8 DW	3.1	2590	2200	1850	1670	1850	1570	1320	1188
								45	5698	4840	4070	3674	4070	3454	2904	2614
								3.4	2730	2320	1950	1760	1950	1650	1390	1251
								49	6006	5104	4290	3872	4290	3630	3058	2752
								3.7	2870	2440	2050	1850	2040	1740	1460	1314
								54	6314	5368	4510	4070	4488	3828	3212	2891
								4.1	3050	2590	2180	1960	2170	1840	1550	1395
								59	6710	5698	4796	4312	4774	4048	3410	3069

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com