



LOAD CERTIFICATES: 200/60-14.5

Brand: ASCENSO

Tread Pattern : IMB 164

Tyre Construction: Bias

LSI : 106 A8

Type: Tube Tyre

Main Applications: Implements

TRA Code : IMP



Salient Features

Specially Designed Rib Pattern:

- Ensures soil protection
- Suitable for both On Road and Off-Road applications
- Built for carrying high loads



Technical Specification

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)			
								Speed, km/h (mph)			
		SW	OD					Mixed application			
		mm	mm					10	25	30	40
		in	in					bar	psi	6	16
200/60-14.5	AG 6.75	205 8.07	608 23.94	283 11.14	1818 71.57	10PR 106 A8	3.7	1110	940	880	790
							54	2442	2068	1936	1738
							4.1	1180	1000	940	840
							59	2596	2200	2068	1848
							4.5	1250	1060	1000	890
							65	2750	2332	2200	1958
							5	1330	1130	1060	950
							73	2926	2486	2332	2090

Note: All tyres conform to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover