



LOAD CERTIFICATES: 200/60-14.5

Brand: ASCENSO

Tread Pattern : IMB 164

Tyre Construction: Bias

LSI : 113 A8

Type: Tube Tyre

Main Applications: Implements

TRA Code : IMP



Salient Features

Specially designed Rib Pattern

- Ensures soil protection
- Suitable for both On Road and Off-Road applications
- Built for carrying high loads



Technical Specification

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)			
								Speed, km/h (mph)			
		SW	OD					Mixed application			
		mm	mm					10	25	30	40
		in	in					bar	psi	6	16
200/60-14.5	AG 6.75	205 8.07	608 23.94	283 11.14	1818 71.57	14PR 113 A8	5.2	1360	1150	1090	970
							75	2992	2530	2398	2134
							5.7	1430	1210	1140	1020
							83	3146	2662	2508	2244
							6.3	1510	1290	1210	1080
							91	3322	2838	2662	2376
							7	1610	1370	1290	1150
							102	3542	3014	2838	2530

Note:All tyres conform to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover