



## LOAD CERTIFICATE : 23.1 - 26

**Brand:** ASCENSO

**Tread Pattern :** PCB 360

**Ply Rating :** 16

**Tyre Construction :** Bias

**Type :** Tubeless

**Main Applications:** Compactor and Combine Harvester

**TRA Code :** R-3



## Salient Features

### **Large Tread Area:**

Increases flotation and minimises  
Ground disturbance in soil compaction  
Operations

### **Optimized Diamond Lug Pattern**

#### **with Sipes:**

Reduces groove cracks and minimises  
slippage

### **Good Rubber Coverage on Tread Base:**

Ensures puncture and impact resistance  
thereby reducing downtime



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Infl. Pres.	Recommended load, kg(lbs)								
								Speed, km/h ( mph)								
		SW	OD	Free Rolling				Drive Wheel								
		mm	mm	10	25			40	50	10	25	40	50			
In	in	in	in	in	in	Bar	Static	6	16	25	31	6	16	25	31	
23.1-26	20	587	1581	710	4729	16 PR 168A8		1.9	12670	6890	5840	5510	5010	6260	5310	5010
		23.1	62.2	28.0	186.2		28	27874	15158	12848	12122	11022	13772	11682	11022	10032
							2.1	13430	7300	6190	5840	5310	6640	5630	5310	4830
							30	29546	16060	13618	12848	11682	14608	12386	11682	10626
							<b>2.3</b>	14170	7700	6530	<b>6160</b>	5610	7000	5940	<b>5600</b>	5100
							<b>33</b>	31174	16940	14366	<b>13552</b>	12342	15400	13068	<b>12320</b>	11220

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6<sup>th</sup> Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)