



LOAD CERTIFICATE : 11.2-20

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque		Static				
		Bar	10					10	20	10		20	30	40	
Psi	6	6	12	6	16	20	25								
11.2-20	W10	284 11.1	1002 39.4	458 18.03	2997 117.9	8 PR 107 A8	1.8	890	1250	1020	1910	1250	1020	890	830
							26	1960	2750	2250	4210	2750	2250	1960	1830
							2	940	1320	1080	2020	1320	1080	940	880
							29	2070	2910	2380	4450	2910	2380	2070	1940
							2.2	1000	1400	1140	2140	1400	1140	1000	930
							32	2200	3080	2510	4710	3080	2510	2200	2050
							2.4	1040	1460	1200	2240	1460	1200	1040	975
							35	2290	3220	2640	4930	3220	2640	2290	2150

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com