



LOAD CERTIFICATE: 11.2-24

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications:2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque						
		mm	mm					mm	mm	Static	10	20	30	40	
in	in	in	in	Bar	10	10	20	Psi	6		6	12	6	16	20
11.2-24	W10	284 11.2	1103 43.4	509 20.0	3299 129.9	8PR 116 A8	2	1180	1650	1350	2530	1650	1350	1180	1100
							29	2600	3630	2970	5570	3630	2970	2600	2420
							2.2	1240	1740	1430	2670	1740	1430	1240	1160
							32	2730	3830	3150	5880	3830	3150	2730	2560
							2.5	1340	1880	1540	2880	1880	1540	1340	1250
							36	2950	4140	3390	6340	4140	3390	2950	2750

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification