



# LOAD CERTIFICATE: 11.2-28

---

**Brand:** ASCENSO

**Tread Pattern :** TDB 120

**Ply Rating :** 8

**Main Applications:** 2WD Tractor

**TRA Code :** R-1



## Salient Features

### **Wider Lugs:**

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

### **Sturdy Sidewall Structure:**

Provides resistance to external damage

### **Strong Nylon Carcass:**

Safeguards the tyre against failures



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		Speed , km/h(mph)													
		Field Operation						Road Operation; Not High and Sustained Torque							
		High Torque	Low Torque												
		Bar	10					10	20	Static	10	20	30	40	
Psi	6	6	12	6	16	20	25								
11.2-28	W10	284 11.2	1205 47.4	560 22.0	3604 141.9	8PR  118 A8	2	1230	1730	1410	2650	1730	1410	1230	1150
							29	2710	3810	3110	5840	3810	3110	2710	2530
							2.2	1310	1830	1500	2810	1830	1500	1310	1220
							32	2890	4030	3300	6190	4030	3300	2890	2690
							2.5	1410	1980	1620	3040	1980	1620	1410	1320
							36	3110	4360	3570	6700	4360	3570	3110	2910

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification