



LOAD CERTIFICATE: 12.4-28

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque		Static	10	20	30	40
		Bar	10					10	20	6		16	20	25	
Psi	6	6	12	6	16	20	25								
12.4-28	W11L	315 12.4	1260 49.6	582 22.9	3769 148.4	8PR 123 A8	1.9	1520	2130	1750	3270	2130	1750	1520	1420
							28	3350	4690	3850	7200	4690	3850	3350	3130
							2.1	1620	2270	1860	3470	2270	1860	1620	1510
							30	3570	5000	4100	7640	5000	4100	3570	3330
							2.2	1660	2330	1910	3570	2330	1910	1660	1550
							32	3660	5130	4210	7860	5130	4210	3660	3410

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification