



LOAD CERTIFICATE : 12.4-36

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications:2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque						
								Bar	10	10	20	Static	10	20	30
Psi	6	6	12	6	16	20	25								
12.4-36	W11L	315 12.4	1464 57.6	684 26.9	4379 172.4	8PR 126 A8	1.9	1670	2340	1920	3590	2340	1920	1670	1560
							28	3680	5150	4230	7910	5150	4230	3680	3440
							2.1	1770	2480	2030	3800	2480	2030	1770	1650
							30	3900	5460	4470	8370	5460	4470	3900	3630
							2.2	1820	2550	2090	3910	2550	2090	1820	1700
							32	4010	5620	4600	8610	5620	4600	4010	3740

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com