



LOAD CERTIFICATE: 13.6-36

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque						
		mm	mm					mm	mm	Bar	10	10	20	Static	10
in	in	in	in	Psi	6	6	12	6	16	20	25				
13.6-36	W12	345 13.6	1514 59.6	705 27.8	4529 178.3	8PR 129 A8	1.7	1850	2600	2130	3980	2600	2130	1850	1730
							25	4070	5730	4690	8770	5730	4690	4070	3810
							1.8	1920	2690	2200	4120	2690	2200	1920	1790
							26	4230	5930	4850	9070	5930	4850	4230	3940
							1.9	1980	2780	2280	4260	2780	2280	1980	1850
							28	4360	6120	5020	9380	6120	5020	4360	4070

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification