



LOAD CERTIFICATE : 13.6-38

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque		Static				
		Bar	10					10	20	10		20	30	40	
Psi	6	6	12	6	16	20	25								
13.6-38	W12	345	1565	730	4681	8PR 131 A8	1.6	1830	2570	2100	3930	2570	2100	1830	1710
							23	4030	5660	4630	8660	5660	4630	4030	3770
							1.7	1890	2660	2180	4070	2660	2180	1890	1770
							25	4160	5860	4800	8960	5860	4800	4160	3900
							1.8	1960	2750	2250	4210	2750	2250	1960	1830
							26	4320	6060	4960	9270	6060	4960	4320	4030
							2	2090	2930	2400	4490	2930	2400	2090	1950
							29	4600	6450	5290	9890	6450	5290	4600	4300

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover