



LOAD CERTIFICATE: 14.9-28

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)										
		SW	OD					Speed , km/h(mph)										
								Field Operation			Road Operation; Not High and Sustained Torque							
		mm	mm					mm	mm	mm	mm	High Torque	Low Torque	Static	10	20	30	40
in	in	in	in	in	in	Psi	6	6	12	6	16	20	25					
14.9-28	W13	378 14.9	1367 53.8	627 24.7	4089 161.0	8PR 130 A8	1.5	1830	2570	2100	3930	2570	2100	1830	1710			
							22	4030	5660	4630	8660	5660	4630	4030	3770			
							1.7	1970	2760	2260	4230	2760	2260	1970	1840			
							25	4340	6080	4980	9320	6080	4980	4340	4050			
							1.8	2030	2850	2340	4370	2850	2340	2030	1900			
							26	4470	6280	5150	9630	6280	5150	4470	4190			

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification