



LOAD CERTIFICATE : 14.9-30

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		Speed , km/h(mph)													
		Field Operation						Road Operation; Not High and Sustained Torque							
		High Torque	Low Torque												
		Bar	10					10	20	Static	10	20	30	40	
Psi	6	6	12	6	16	20	25								
14.9-30	W13	378 14.8	1418 55.8	652 25.6	4241 166.9	8PR 17 A8	1.5	1680	2360	1930	3610	2360	1930	1680	1570
							22	3700	5200	4250	7950	5200	4250	3700	3460
							1.6	1740	2450	2000	3750	2450	2000	1740	1630
							23	3830	5400	4410	8260	5400	4410	3830	3590
							1.7	1810	2540	2080	3890	2540	2080	1810	1690
							25	3990	5590	4580	8570	5590	4580	3990	3720
							1.8	1870	2630	2150	4030	2630	2150	1870	1750
							26	4120	5790	4740	8880	5790	4740	4120	3850

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com