



## LOAD CERTIFICATE: 15.5-38

---

**Brand:** ASCENSO

**Tread Pattern :** TDB 120

**Ply Rating :** 8

**Main Applications:** 2WD Tractor

**TRA Code :** R-1



## Salient Features

### **Wider Lugs:**

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

### **Sturdy Sidewall Structure:**

Provides resistance to external damage

### **Strong Nylon Carcass:**

Safeguards the tyre against failures



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque						
		mm	mm					mm	mm	Bar	10	10	20	Static	10
in	in	in	in	Psi	6	6	12	6	16	20	25				
15.5-38	W14L	394 15.5	1569 61.8	732 28.8	4693 184.8	8PR  133 A8	1.5	1980	2780	2280	4260	2780	2280	1980	1850
							22	4360	6120	5020	9380	6120	5020	4360	4070
							1.6	2050	2880	2360	4420	2880	2360	2050	1920
							23	4520	6340	5200	9740	6340	5200	4520	4230
							<b>1.8</b>	2200	3090	2530	4740	3090	2530	2200	<b>2060</b>
							26	4850	6810	5570	10440	6810	5570	4850	4540

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification