



# LOAD CERTIFICATE: 16.9-28

**Brand:** ASCENSO

**Tread Pattern :** TDB 120

**Ply Rating :** 8

**Main Applications:** 2WD Tractor

**TRA Code :** R-1



## Salient Features

### **Wider Lugs:**

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

### **Sturdy Sidewall Structure:**

Provides resistance to external damage

### **Strong Nylon Carcass:**

Safeguards the tyre against failures



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		Speed , km/h(mph)													
		Field Operation						Road Operation; Not High and Sustained Torque							
		High Torque	Low Torque												
		Bar	10					10	20	Static	10	20	30	40	
Psi	6	6	12	6	16	20	25								
16.9-28	W15L	429 16.9	1435 56.5	655 25.8	4292 169.0	8PR  135 A8	1.5	2200	3090	2530	4740	3090	2530	2200	2060
							22	4850	6810	5570	10440	6810	5570	4850	4540
							<b>1.65</b>	2330	3270	2680	5010	3270	2680	2330	<b>2180</b>
							24	5130	7200	5900	11040	7200	5900	5130	4800

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification