



# LOAD CERTIFICATE: 18.4-34

---

**Brand:** ASCENSO

**Tread Pattern :** TDB 120

**Ply Rating :** 8

**Main Applications:** 2WD Tractor

**TRA Code :** R-1



## Salient Features

### **Wider Lugs:**

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

### **Sturdy Sidewall Structure:**

Provides resistance to external damage

### **Strong Nylon Carcass:**

Safeguards the tyre against failures



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque		Static	10	20	30	40
		Bar	10					10	20	10		20	30	40	
Psi	6	6	12	6	16	20	25								
18.4-34	W16L	467 18.4	1654 65.1	758 29.8	4947 194.8	8PR 142 A8	1.2	2590	3630	2980	5570	3630	2980	2590	2420
							17	5700	8000	6560	12270	8000	6560	5700	5330
							1.3	2720	3810	3120	5840	3810	3120	2720	2540
							19	5990	8390	6870	12860	8390	6870	5990	5590
							<b>1.4</b>	2840	3980	3260	6100	3980	3260	2840	<b>2650</b>
							20	6260	8770	7180	13440	8770	7180	6260	5840

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification