



LOAD CERTIFICATE : 8.3-20

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 6

Main Applications:2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque		Static				
		Bar	10					10	20	10		20	30	40	
Psi	6	6	12	6	16	20	25								
8.3-20	W6	211 8.3	893 35.2	413 16.3	2671 105.2	6 PR 92 A8	1.8	580	810	660	1240	810	660	580	540
							26	1280	1780	1450	2730	1780	1450	1280	1190
							2	610	860	700	1310	860	700	610	570
							29	1340	1890	1540	2890	1890	1540	1340	1260
							2.2	640	900	740	1380	900	740	640	600
							32	1410	1980	1630	3040	1980	1630	1410	1320
							2.4	670	950	770	1450	950	770	670	630
							35	1480	2090	1700	3190	2090	1700	1480	1390

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com