



LOAD CERTIFICATE: 9.5-24

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		SW	OD					Speed , km/h(mph)							
								Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque						
		mm	mm					mm	mm	Bar	10	10	20	Static	10
in	in	in	in	Psi	6	6	12	6	16	20	25				
9.5-24	W8	241 9.5	1048 41.3	486 19.1	3135 123.4	8PR 112 A8	2.3	1070	1500	1230	2300	1500	1230	1070	1000
							33	2360	3300	2710	5070	3300	2710	2360	2200
							2.5	1120	1580	1290	2420	1580	1290	1120	1050
							36	2470	3480	2840	5330	3480	2840	2470	2310
							2.8	1200	1680	1380	2580	1680	1380	1200	1120
							41	2640	3700	3040	5680	3700	3040	2640	2470

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification