



# LOAD CERTIFICATE: 480/65R24

**Brand:** ASCENSO

**Tread Pattern :** TDR 650

**Tyre Construction:** Radial

**LSI :** 140 D

**Type:** Tube Less

**Main Applications:** 4WD Tractor

**TRA Code :** R-1W



## Salient Features

### **Optimum Tread Design:**

Maximum performance in field and on road operations

### **First in the Industry with Dual Mud Breakers:**

Ensure better self-cleaning

### **Greater Lug Overlap:**

Provides safe and comfortable ride at high speeds



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
								Mixed application						
								Bar	Static	10	25	30	40	50
		mm	mm	mm	mm		Psi		6	16	19	25	31	40
		in	in	in	in									
480/65 R 24	W15L	479 18.8	1234 48.5	563 22.1	3691 145.3	140 D	1.2	3450	2250	1780	1730	1640	1580	1500
							17	7600	4960	3920	3810	3610	3480	3300
							1	3840	2510	1980	1920	1830	1750	1670
							20	8460	5530	4360	4230	4030	3850	3680
							1.7	4420	2880	2280	2210	2100	2020	1920
							25	9740	6340	5020	4870	4630	4450	4230
							2.1	5180	3380	2670	2590	2460	2360	2250
							30	11410	7440	5880	5700	5420	5200	4960
							2.4	5750	3750	2960	2880	2740	2630	2500
35	12670	8260	6520	6340	6040	5790	5510							

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6<sup>th</sup> Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)