



LOAD CERTIFICATE: 480/65R28

Brand: ASCENSO

Tread Pattern : TDR 650

Tyre Construction: Radial

LSI : 142 D

Type: Tube Less

Main Applications: 4WD Tractor

TRA Code : R-1W



Salient Features

Optimum Tread Design:

Maximum performance in field and on road operations

First in the Industry with Dual Mud Breakers:

Ensure better self-cleaning

Greater Lug Overlap:

Provides safe and comfortable ride at high speeds



Technical Specification

Size	W	Rim	Unloaded Dimension		SLR	RC	Load Index	PR Symbols	Recommended load, kg (lbs)									
			SW	OD					mm	mm	mm	mm	Speed, km/h (mph)					
													Mixed application					
													Bar	Static	10	25	30	40
Psi		6	16	19	25	31	40											
480/65 R 28	W15L	479 18.8	1335 52.5	613 24.1	3993 157.2	142 D	1.2	3660	2390	1880	1830	1740	1670	1590				
							17	8060	5260	4140	4030	3830	3680	3500				
							1	4070	2660	2100	2040	1940	1860	1770				
							20	8960	5860	4630	4490	4270	4100	3900				
							1.7	4690	3060	2420	2350	2230	2140	2040				
							25	10330	6740	5330	5180	4910	4710	4490				
							2.1	5500	3590	2830	2750	2620	2510	2390				
							30	12110	7910	6230	6060	5770	5530	5260				
							2.4	6100	3980	3140	3050	2900	2780	2650				
							35	13440	8770	6920	6720	6390	6120	5840				

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com