



# LOAD CERTIFICATE: 540/65R34

**Brand:** ASCENSO

**Tread Pattern :** TDR 650

**Tyre Construction:** Radial

**LSI :** 152 D

**Type:** Tube Less

**Main Applications:** 4WD Tractor

**TRA Code :** R-1W



## Salient Features

### **Optimum Tread Design:**

Maximum performance in field and on road operations

### **First in the Industry with Dual Mud Breakers:**

Ensure better self-cleaning

### **Greater Lug Overlap:**

Provides safe and comfortable ride at high speeds



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
								Mixed application						
								Bar	Static	10	25	30	40	50
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm		
in	in	in	in	in	in	in	Psi	6	16	19	25	31	40	
540/65 R 34	W16L	530 20.8	1566 61.6	722 28.4	4684 184.4	152 D	1.2	4900	3200	2520	2450	2330	2240	2130
							17	10790	7050	5550	5400	5130	4930	4690
							1	5450	3560	2810	2730	2600	2490	2370
							20	12000	7840	6190	6010	5730	5480	5220
							1.7	6280	4100	3240	3140	2990	2870	2730
							25	13830	9030	7140	6920	6590	6320	6010
							2.1	7360	4800	3790	3680	3500	3360	3200
							30	16210	10570	8350	8110	7710	7400	7050
							2.4	8170	5330	4210	4080	3890	3730	3550
							35	18000	11740	9270	8990	8570	8220	7820

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6<sup>th</sup> Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)