



LOAD CERTIFICATE: 650/65R38

Brand: ASCENSO

Tread Pattern : TDR 650

Tyre Construction: Radial

LSI : 163 D

Type: Tube Less

Main Applications: 4WD Tractor

TRA Code : R-1W



Salient Features

Optimum Tread Design:

Maximum performance in field and on road operations

First in the Industry with Dual Mud Breakers:

Ensure better self-cleaning

Greater Lug Overlap:

Provides safe and comfortable ride at high speeds



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
								Mixed application						
								Bar	Static	10	25	30	40	50
mm	mm	mm	mm	Psi	6	16	19	25	31	40				
in	in	in	in											
650/65 R 38	DW20B	645 25.4	1811 71.3	832 32.7	5417 213.3	163 D	1.2	6740	4400	3470	3370	3210	3080	2930
							17	14850	9690	7640	7420	7070	6780	6450
							1	7480	4880	3850	3740	3560	3410	3250
							20	16480	10750	8480	8240	7840	7510	7160
							1.7	8600	5610	4430	4300	4100	3930	3740
							25	18940	12360	9760	9470	9030	8660	8240
							2.1	10100	6590	5200	5050	4810	4610	4390
							30	22250	14520	11450	11120	10590	10150	9670
							2.4	11210	7310	5780	5610	5340	5120	4875
							35	24690	16100	12730	12360	11760	11280	10740

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com