



LOAD CERTIFICATE: 650/65R42

Brand: ASCENSO

Tread Pattern : TDR 650

Tyre Construction: Radial

LSI : 165 D

Type: Tube Less

Main Applications: 4WD Tractor

TRA Code : R-1W



Salient Features

Optimum Tread Design:

Maximum performance in field and on road operations

First in the Industry with Dual Mud Breakers:

Ensure better self-cleaning

Greater Lug Overlap:

Provides safe and comfortable ride at high speeds



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)									
		SW	OD					Speed, km/h (mph)									
								Mixed application									
								Bar	Static	10	25	30	40	50	65		
		mm	mm	mm	mm		Psi										
		in	in	in	in												
650/65 R 42	DW20B	645 25.4	1913 75.3	883 34.7	5722 225.2	165 D	1.2	7110	4640	3660	3550	3380	3240	3090			
							17	15660	10220	8060	7820	7440	7140	6810			
							1	7890	5150	4060	3940	3760	3600	3430			
							20	17380	11340	8940	8680	8280	7930	7560			
							1.7	9090	5930	4680	4540	4330	4150	3950			
							25	20020	13060	10310	10000	9540	9140	8700			
							2.1	10670	6960	5500	5340	5080	4870	4640			
							30	23500	15330	12110	11760	11190	10730	10220			
							2.4	11850	7730	6100	5920	5640	5410	5150			
35	26100	17030	13440	13040	12420	11920	11340										

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com