



LOAD CERTIFICATE: 6.00-19

Brand: ASCENSO

Tread Pattern : TSB 110

Ply Rating : 6

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code: F2



Salient Features

Wider Centre Rib:

Ease in steering & prevents damage to the grass land

High Strength Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
		mm	mm	mm	mm		Mixed Application						
		in	in	in	in		Bar	Static	10	20	25	30	40
				Psi	6	12	15		20	25			
6.00-19	4.50E	165	815	379	2438	6PR	2.7	1470	980	680	630	540	490
							39	3240	2160	1500	1390	1190	1080
							3.0	1560	1040	720	670	580	520
							44	3440	2290	1590	1480	1280	1150
		6.5	32.1	14.9	96.0	89 A8	3.3	1650	1100	760	700	610	550
							48	3630	2420	1670	1540	1340	1210
							3.6	1740	1160	800	740	640	580
							52	3830	2560	1760	1630	1410	1280

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification