



LOAD CERTIFICATE: 6.50-16

Brand: ASCENSO

Tread Pattern : TSB 110

Ply Rating : 6

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code: F2



Salient Features

Wider Centre Rib:

Ease in steering & prevents damage to the grass land

High Strength Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
		mm	mm					Mixed Application					
		in	in					mm	mm	mm	mm	mm	mm
		in	in					in	in	in	in	in	in
6.50-16	4.00E	173 6.8	761 29.9	350 13.8	2276 89.6	6 PR 88 A8	Bar	Static	10	20	25	30	40
							Psi		6	12	15	20	25
							2.5	1440	960	660	610	530	480
							36	3170	2110	1450	1340	1170	1060
							2.7	1500	1000	690	640	560	500
							39	3300	2200	1520	1410	1230	1100
							3.0	1590	1060	730	680	590	530
							44	3500	2330	1610	1500	1300	1170
3.3	1680	1120	770	720	620	560							
48	3700	2470	1700	1590	1370	1230							

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover